



NORHTFIELD SERIES

AREA LIGHTING | PENDANT MOUNT



SPECIFICATIONS

LUMINAIRE Heavy wall, corrosion resistant aluminum construction.

DRIVER Electronic LED driver, 120-277V.
Options: 480V driver, dimming control 0-10V

ELECTRICAL All components UL recognized. Luminaire shipped complete and ready to install.

FINISH Powder coat - Standard colors are Black, White, Dark Green, and Dark Bronze.
Custom colors available, consult factory.
All exposed hardware shall be stainless steel.

FEATURES + BENEFITS

- Industry leading LED systems
- High efficiency and energy saving
- Environmentally friendly
- Reliable and low-maintenance
- 7-year limited warranty
- UL listed electrical components
- ***Suitable for wet locations***

ORDER INFORMATION

EXAMPLE: NFD-80W-35K-SMT-OPL V-PM-BLK-DIM

SERIES	WATTAGE	COLOR TEMP.	VOLTAGE	OPTICS	MOUNTING	FINISH	OPTIONS
NORTHFIELD (NFD)	5W-80W PLEASE SPECIFY	2700K (27K) 3000K (3K) 3500K (35K) 4000K (4K) 5000K (5K) CUSTOM COLOR TEMP. CONSULT FACTORY	SMT 120-277V 480V	FLAT LENSE (FL) TYPE II TYPE III TYPE IV TYPE V OPAL DOME (OPL) TYPE V	PENDANT MOUNT (PM) WALL MOUNT (WM) PLEASE SPECIFY TENON SIZE OR POLE DIA.	BLACK (BLK) WHITE (WHT) GREEN (GRN) DARK BRONZE (DBZ) RAL COLORS AVAILABLE (CONSULT FACTORY)	DIM 0-10V DIMMING BPC BUTTON PHOTO-CELL



ECHO LIGHTING, INC
*Designers and Manufacturers
of Outdoor Lighting*

Ph.: +1-323-890-9008
Email: info@echoltg.com

5618 E. Washington Blvd.
Commerce, CA 90040
www.echolighting.com